

ZEETEX THUNDER PLUS DIESEL ENGINE OIL

SAE GRADE: 15W/40,20W/50

PERFORMANCE LEVEL:

API classification: CI-4/SL

European specification: ACEA E5/B3/A2,
MB 228.1/229.1, VOLVO VDS 3, M3275, MACK EO-M

- ZEETEX THUNDER PLUS DIESEL ENGINE OIL is a top-of-the-line diesel engine oil formulated with a select mixture of additives and base oil. They are recommended for all naturally and turbo charged diesel engines, used in heavy duty trucks, agricultural, mining and construction equipment as well as gasoline run turbo charged vehicles. It is designed for extended drain intervals in diesel powered on and off road equipments.
- ZEETEX THUNDER PLUS DIESEL ENGINE OIL exceeds industry standards in terms of excellent high temperature deposit control, oil thickening resistance, soot dispersant qualities and oil consumption control. Presence of detergent additives in the oil provides maximum lubricant alkalinity and alkalinity retention leading to cleaner engines.

PHYSICAL CHARACTERISTICS	TEST METHOD	SAE GRADE/TYPICAL VALUE	
		15W/40	20W/50
Specific Gravity @ 60/60 °F	ASTM D-4052	0.888	0.895
Viscosity Kinematic, cSt @ 40 °C	ASTM D-445	111	160
Viscosity Kinematic, cSt @ 100 °C	ASTM D-445	15.5	18.5
Viscosity Index	ASTM D-2270	140	130
Flash Point, COC, °C	ASTM D-92	220	230
Pour Point °C	ASTM D-97	-27	-24
TBN, mg KOH/g	ASTM D-2896	11.0	11.0
Sulphated Ash, %wt	ASTM D-874	1.00	1.00