

# ZEETEX TURBO PLUS DIESEL ENGINE OIL

SAE GRADE: 15W/40

PERFORMANCE LEVEL:

API classification: CG-4/SJ

European specification: ACEA A3/B3 MB 228.1, VOLVO VDS, MAN 271

U.S. Military Specification: MIL-L-2104E, MIL-L-46152D

- ZEETEX TURBO PLUS DIESEL ENGINE OIL is a premium quality commercial mixed fleet engine oil formulated from high quality mineral base oil and a superior balanced additive system to meet the demand of modern diesel and gasoline engines. It is recommended for use in modern on and off highway diesel engines, and for use in gasoline engines thereby offering one oil for mixed fleet operators.
- ZEETEX TURBO PLUS DIESEL ENGINE OIL provides good protection against oil thickening, high temperature engine deposits, sludge build up, oil degradation and corrosion. Good level of cleanliness, soot control and wear protection in turbo and non turbo charged engines contribute to longer engine life.

PHYSICAL CHARACTERISTICS	TEST METHOD	SAE GRADE/TYPICAL VALUE
		15W/40
Specific Gravity @ 60/60 °F	ASTM D-4052	0.886
Viscosity Kinematic, cSt @ 40 °C	ASTM D-445	108
Viscosity Kinematic, cSt @ 100 °C	ASTM D-445	14.5
Viscosity Index	ASTM D-2270	138
Flash Point, COC, °C	ASTM D-92	220
Pour Point °C	ASTM D-97	-27
TBN, mg KOH/g	ASTM D-2896	11
Sulphated Ash, %wt	ASTM D-874	1.5