

ZEETEX POWER PLUS DIESEL ENGINE OIL

SAE GRADE: 40,50

PERFORMANCE LEVEL:

API classification: CF/SF

European specification: CAT-TO2, CCMC G1/G2,D1/D2

U.S. Military specification: MIL-L-2104D, MIL-L-46152B

- ZEETEX POWER PLUS DIESEL ENGINE OIL is a blend of superior quality paraffin base stock and specially selected additive package. It is recommended for use in turbo charged and naturally aspirated diesel engine for cars, pickup and trucks. It is suitable for gasoline engines where API SF grade is recommended.
- ZEETEX POWER PLUS DIESEL ENGINE OIL has excellent detergent-dispersant ability to keep the engine clean and give extended drain. It has excellent viscosity index improver and pour point depressant to operate in extreme conditions. It contains effective package of anti-wear, anti-rust and anti-corrosion which grant longer engine life. It has good startability at low temperature and excellent control over sludge formation.

PHYSICAL CHARACTERISTICS	TEST METHOD	SAE GRADE/TYPICAL VALUE	
		40	50
Specific Gravity @ 60/60 °F	ASTM D-4052	0.892	0.903
Viscosity Kinematic, cSt @ 40 °C	ASTM D-445	160	209
Viscosity Kinematic, cSt @ 100 °C	ASTM D-445	15.7	18.7
Viscosity Index	ASTM D-2270	100	99
Flash Point, COC, °C	ASTM D-92	240	250
Pour Point °C	ASTM D-97	-15	-12
TBN, mg KOH/g	ASTM D-2896	10	10
Sulphated Ash, %wt	ASTM D-874	1.40	1.40