

ZEETEX 2T OIL

SAE GRADE: 30

PERFORMANCE LEVEL:

API Service Classification: TC

- ZEETEX 2T OIL is super quality oil for gasoline powered two stroke cycle engines. It is a blend of highly refined paraffinic base stock and additive package formulated to meet the requirement of high speed two stroke engines. It is specially formulated for use in high powered air cooled two stroke cycle engines used in chain saws, lawn mowers, heavy duty motor cycles and one or two cylinder small outboard engines.
- ZEETEX 2T OIL can be used in engines where oil is mixed with petrol or a separate injector is provided for mixing.
- ZEETEX 2T OIL has high thermal stability and gives low heat generation and less frictional power losses. It has good resistance to oxidation to keep the engine free from carbon deposits, and gives trouble-free ignition to provide longer spark plug life. It mixes easily with petrol and the mix remains stable to provide better engine lubrication. It produces less deposit, giving clean rings and spark plugs, less gumming and a cleaner exhaust.

PHYSICAL CHARACTERISTICS	TEST METHOD	SAE GRADE/TYPICAL VALUE
		30
Specific Gravity @ 60/60 °F	ASTM D-4052	0.865
Viscosity Kinematic, cSt @ 40 °C	ASTM D-445	85
Viscosity Kinematic, cSt @ 100 °C	ASTM D-445	11.5
Viscosity Index	ASTM D-2270	126
Flash Point, COC, °C	ASTM D-92	110
Pour Point °C	ASTM D-97	-30
Sulphated Ash, %wt	ASTM D-874	<0.10