

ZEETEX MP GEAR OIL

SAE GRADE: 80W/90, 85W/140, 90, 140

PERFORMANCE LEVEL:

API classification: GL-5

U.S. Military specification: MIL-L-2105D

- ZEETEX MP GEAR OIL is a high performance, multipurpose, thermally stable, extreme pressure automotive gear lubricant, blended from superior quality paraffinic base oil and selected extreme pressure additive package.
- ZEETEX MP GEAR OIL is recommended for automotive hypoid gear differentials operating under high speed and/or low speed, high torque conditions, and heavy-duty, non-synchronized manual transmission and trans axle. Its highly refined base oil and special inhibitor system provide excellent oxidation stability, while presence of sulphur-phosphorous E.P. additive system provides excellent load carrying capability.

PHYSICAL CHARACTERISTICS	TEST METHOD	SAE GRADE/TYPICAL VALUE			
		80W/90	85W/140	90	140
Specific Gravity @ 60/60 °F	ASTM D-4052	0.885	0.90	0.90	.908
Viscosity Kinematic, cSt @ 40 °C	ASTM D-445	150	410	170	425
Viscosity Kinematic, cSt @ 100 °C	ASTM D-445	15	28	16	29
Viscosity Index	ASTM D-2270	100	98	97	97
Flash Point, COC, °C	ASTM D-92	220	234	226	240
Pour Point °C	ASTM D-97	-27	-24	-9	-9
Foam Sequence I (ml)	ASTM D-892	5/0	10/0	0/0	0/0
Foam Sequence II (ml)	ASTM D-892	10/0	10/0	10/0	10/0
Foam Sequence III (ml)	ASTM D-892	5/0	10/0	0/0	0/0