

# ZEETEX LAZER Hi SPEED ENGINE OIL (Fully Synthetic)

SAE GRADE: 5W/30, 10W/40

PERFORMANCE LEVEL:

API classification: SL/CF

European specification: ACEA A4-98,B4-98,M.B 229.3,  
VW 502/505, BMW, Porche.

- ZEETEX LAZER Hi SPEED ENGINE OIL is a fully synthetic crank case oil that is ideal for most modern and advanced high performance engines to achieve peak performance.
- ZEETEX LAZER Hi SPEED ENGINE OIL ensures maximum engine protection through superior viscosity retention, high oxidation resistance and excellent thermal stability. Maximum engine cleanliness, smooth control and wear protection contribute to longer engine life and greater fuel efficiency.

PHYSICAL CHARACTERISTICS	TEST METHOD	SAE GRADE/TYPICAL VALUE	
		5W/30	10W/40
Specific Gravity @ 60/60 °F	ASTM D-4052	0.850	0.855
Viscosity Kinematic, cSt @ 40 °C	ASTM D-445	69	98
Viscosity Kinematic, cSt @ 100 °C	ASTM D-445	11.5	14.5
Viscosity Index	ASTM D-2270	161	153
Flash Point, COC, °C	ASTM D-92	220	224
Pour Point °C	ASTM D-97	-49	-45
TBN, mg KOH/g	ASTM D-2896	9.0	9.0
CCS @ -30 °C, cp	ASTM D-5293	4400	-
CCS @ -25 °C, cp	ASTM D-5293	-	5000