

# ZEETEX LAZER 6000 MOTOR OIL

SAE GRADE: 20W/50

PERFORMANCE LEVEL:

API classification: SG/CD

European specification: CCMC G4/PD-2

U.S Military specification: MIL-L 46152 D

- ZEETEX LAZER 6000 MOTOR OIL is a high quality multigrade engine oil for use in naturally aspirated or turbo charged engines. Although primarily developed for gasoline engines, it is equally suitable for diesel engines of passenger cars and light vehicles.
- ZEETEX LAZER 6000 MOTOR OIL will provide excellent protection against wear and corrosion. It has superior resistance to oxidation and excellent multigrade stability in service. It reduces maintenance cost through excellent resistance to oil degradation.

PHYSICAL CHARACTERISTICS	TEST METHOD	SAE GRADE/TYPICAL VALUE
		20W/50
Specific Gravity @ 60/60 °F	ASTM D-4052	0.890
Viscosity Kinematic, cSt @ 40 °C	ASTM D-445	148
Viscosity Kinematic, cSt @ 100 °C	ASTM D-445	17.9
Viscosity Index	ASTM D-2270	126
Flash Point, COC, °C	ASTM D-92	230
Pour Point °C	ASTM D-97	-24
TBN, mg KOH/g	ASTM D-2896	7.0
Sulphated Ash, %wt	ASTM D-874	1.00