

ZEETEX LAZER 5000 MOTOR OIL

SAE GRADE: 20W/50, 40

PERFORMANCE LEVEL:

API classification: SF/CD

U.S Military specification: MIL-L 46152 B
MIL-L 2104 D

- ZEETEX LAZER 5000 MOTOR OIL is a superior quality crank case oil and is a blend of highly refined base stock and an excellent additive package. ZEETEX LAZER 5000 MOTOR OIL is recommended for use in naturally aspirated or turbo duty charged gasoline and diesel engines of passenger cars and light vehicles.
- ZEETEX LAZER 5000 MOTOR OIL gives good startability at low temperature and provides outstanding protection against rust and corrosion. It maintains oxidation resistance and high thermal stability in wide temperature range and gives excellent performance year round even under severe driving conditions.

PHYSICAL CHARACTERISTICS	TEST METHOD	SAE GRADE/TYPICAL VALUE	
		20W/50	40
Specific Gravity @ 60/60 °F	ASTM D-4052	0.890	0.892
Viscosity Kinematic, cSt @ 40 °C	ASTM D-445	155	156
Viscosity Kinematic, cSt @ 100 °C	ASTM D-445	18.5	15.6
Viscosity Index	ASTM D-2270	124	99
Flash Point, COC, °C	ASTM D-92	230	240
Pour Point °C	ASTM D-97	-24	-9
TBN, mg KOH/g	ASTM D-2896	6	6
Sulphated Ash, %wt	ASTM D-874	0.93	0.93