

- ZEETEX CIRCULATING OIL is a top quality circulating oil. It is based on superior quality natural high viscosity index solvent redefined paraffinic base stock with special foam inhibitors.
- ZEETEX CIRCULATING OIL is recommended for systems operating under mild conditions. It can be used in hydraulic systems, pumps, enclosed industrial gears and bearings where oxidation resistance and anti-wear is not of prime significance. It is suitable for industrial applications where oil losses are high and heavy contamination requires frequent oil change.

| PHYSICAL CHARACTERISTICS          | TEST METHOD | ISO GRADE/TYPICAL VALUE |       |       |       |       |       |
|-----------------------------------|-------------|-------------------------|-------|-------|-------|-------|-------|
|                                   |             | 32                      | 46    | 68    | 100   | 220   | 320   |
| Specific Gravity @ 60/60 °F       | ASTM D-4052 | 0.870                   | 0.875 | 0.882 | 0.885 | 0.896 | 0.898 |
| Viscosity Kinematic, cSt @ 40 °C  | ASTM D-445  | 32                      | 45    | 66    | 99    | 225   | 318   |
| Viscosity Kinematic, cSt @ 100 °C | ASTM D-445  | 5.4                     | 6.7   | 8.5   | 11.0  | 19.0  | 24.2  |
| Viscosity Index                   | ASTM D-2270 | 102                     | 97    | 95    | 95    | 95    | 95    |
| Flash Point, COC, °C              | ASTM D-92   | 210                     | 220   | 230   | 238   | 245   | 250   |
| Pour Point °C                     | ASTM D-97   | -15                     | -15   | -12   | -12   | -9    | -9    |